



Welder's First Choice

# SAFETY DATA SHEET

PAGE 1

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

## SECTION - 1 IDENTIFICATION

### Product Identifier

**Trade Name:** Carbon and Low-Alloy Steel Rods for Oxyfuel Gas Welding.

**Product Number:**

**Specification:** A5.2

**Classification:** R45, R60

**Carbon steel coated welding electrodes Specification:** A5.2

**Classification:** R45, R60

Low hydrogen carbon steel coated welding electrodes

**Relevant identified uses of the substance or mixture and uses advised against:**

For professional use only. Use according to manufacturer's specification.

**Product Description:** Carbon and Low-Alloy Steel Rods for Oxyfuel Gas Welding.

**Application of the substance/the mixture :** Industry specific application.

**Details of the Supplier of the Safety Data Sheet:**

**Manufacturer/Supplier:**

ROYALE WELDWELL PVT LTD

No.02, Uthiramerur Road, Malaipalayam Post, Maduranthagam, Chengelpet, Dist. Tamilnadu-603303 (INDIA)

**Telephone:**+91-9840441459

2Hazard(s)Identification

**Emergency telephone number:** +91-9840441459

## SECTION - 2 HAZARD(S) IDENTIFICATION

· **Classification of the substance or mixture:**



**Skin Irrit. 2 H315** Causes skin irritation.

**STOT SE 3H335** May cause respiratory irritation.

**Eye Irrit. 2B H320** Causes eye irritation.

· **Label elements:**

**Hazard pictograms:**



**Signal word: Danger**

· **Hazard-determining components of labelling:**

Iron

Copper

**Hazard statements:**

**H315+H320:** Causes skin and eye irritation.

**H335:** May cause respiratory irritation.

**Precautionary statements:**

**P261:** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P264:** Wash thoroughly after handling.

**P271:** Use only outdoors or in a well-ventilated area.

**P280:** Wear protective gloves.



# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

Welder's First Choice

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

**P302+P352:** If on skin: Wash with plenty of water.

**P304+P340:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**P305+P351+P338:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P312:** Call a poison centre/doctor if you feel unwell.

**P321:** Specific treatment(see supplementary first aid instructions on this Safety Data Sheet).

**P362+P364:**Take off contaminated clothing and wash it before reuse.

**P332+P313:** If skin irritation occurs: Get medical advice/attention.

**P337+P313:** If eye irritation persists: Get medical advice/attention.

**P403+P233:** Store in a well-ventilated place. Keep container tightly closed.

**P405:** Store locked up.

**P501:** Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Unknown acute toxicity:**

This value refers to knowledge of known, established toxicological or ecotoxicological values. 1 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health= 1  
Fire = 0  
Reactivity = 0

**HMIS-ratings (scale 0 - 4)**



Health= 1 Fire = 0  
Physical Hazard= 0

**Hazard(s) not otherwise classified (HNOC): None known**

## SECTION -3 COMPOSITION/INFORMATION ON INGREDIENTS

**·Chemical characterization: Mixtures**

**· Description: Mixture of substances listed below with non-hazardous additions.**

**Dangerous Components:**

CAS: 7439-89-6 RTECS: NO 4565500	Iron Flam. Sol.2, H228; Skin Irrit.2, H315; STOT SE 3, H335; EyeIrrit. 2B, H320; Combustible Dust	95-99%
CAS: 7439-96-5 RTECS: OO 9275000	Manganese Pyr. Sol. 1, H250; Water-react. 1, H260	0.5-3%
CAS: 7440-21-3	Silicon Flam. Sol.2, H228; Acute Tox. 4, H302; EyeIrrit. 2B, H320; Combustible Dust	0.1-1%
CAS: 7440-50-8 RTECS: GL 5325000	Copper Flam. Sol.1, H228; Chronic 4, H413; STOT SE 3, H335; Aquatic Acute 3, H402; Aquatic	0.1-1%

**· Additional information:**

the exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

Note: Certain chemical constituents listed in Section 3 may vary depending upon the Classification of the Carbon Steel Electrodes for Shielded Metal Arc Welding products



# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

Welder's First Choice

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

## SECTION -4 FIRST-AID MEASURES

### Description of first aid measures

#### General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

· **After inhalation:** In case of unconsciousness place patient stably in the side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

· **After eye contact:** Do NOT rub eyes. Immediately rinse opened eye(s) for at least 15 minutes under running water, lifting upper and lower lids occasionally. If symptoms persist, consult a physician.

If easy to do so, remove contact lenses if worn.

· **After swallowing:** Rinse out mouth and then drink plenty of water. Do not induce vomiting without medical advice. If swallowed and symptoms occur, consult a doctor.

#### Information for doctor

· Most important symptoms and effects, both acute and delayed: No further relevant information available.

· Indication of any immediate medical attention and special treatment needed:

## SECTION -5 FIRE-FIGHTING MEASURES

### Extinguishing media

· **Suitable extinguishing agents:** Use firefighting measures that suit the environment.

· For safety reasons unsuitable extinguishing agents: No further relevant information.

#### Special hazards arising from the substance or mixture:

Amorphous or crystalline silicon both react exothermically when heated with alkali-metal carbonates attaining incandescence and evolving carbon monoxide.

Material in powder form, capable of creating a dust explosion. Mixture of silicon, aluminium, and lead oxide explodes when heated.

#### Advice for firefighters

#### Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

#### Additional information:

These items are not reactive, flammable, or explosive and essentially not hazardous at ambient temperatures.

Welding arcs and sparks can ignite combustibles and flammable products. If involved in a fire, these products

may generate irritating aluminium fumes and a variety of metal oxides. Emergency responders must wear

personal protection equipment suitable for the situation. Use the extinguishing media recommended for the

burning materials and fire situation. See ANSI Z49.1 "Safety in Welding and Cutting" and "Safe Practices" Code: SP, published by the American Welding Society.

## SECTION -6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Wear protective equipment. Keep unprotected persons away

#### Environmental precautions:

Do not allow to enter sewers/surface or ground water.

#### Methods and material for containment and cleaning up:

Pick up mechanically.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.



# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

Welder's First Choice

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

**Reference to other sections:**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.  
Protective Action Criteria for Chemicals

<b>PAC-1:</b>		
7439-89-6	Iron	3.2 mg/m <sup>3</sup>
7439-96-5	Manganese	3 mg/m <sup>3</sup>
7440-21-3	Silicon	45 mg/m <sup>3</sup>
7440-50-8	Copper	3 mg/m <sup>3</sup>
<b>PAC-2:</b>		
7439-89-6	Iron	35 mg/m <sup>3</sup>
7439-96-5	Manganese	5 mg/m <sup>3</sup>
7440-21-3	Silicon	100 mg/m <sup>3</sup>
7440-50-8	Copper	33 mg/m <sup>3</sup>
<b>PAC-3:</b>		
7439-89-6	Iron	150 mg/m <sup>3</sup>
7439-96-5	Manganese	1,800 mg/m <sup>3</sup>
7440-21-3	Silicon	630 mg/m <sup>3</sup>
7440-50-8	Copper	200 mg/m <sup>3</sup>

## SECTION -7 HANDLING AND STORAGE

**Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.

**Information about protection against explosions and fires:** Keep protective respiratory device available.

**Conditions for safe storage:** including any incompatibilities Store away from strong acids, strong bases, strong oxidizing agents and strong reducing agents.

**Storage Requirements to be met by storerooms and receptacles:** Store in the original container.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep receptacle tightly sealed.

**Specific end use(s):**No further relevant information available.

## SECTION -8 EXPOSURE CONTROLS/PERSONAL PROTECTION

· Additional information about design of technical systems: No further data; see section 7.

**Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

**Components with occupational exposure limits:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits



# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

Welder's First Choice

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

### 7439-96-5 Manganese

PEL	Ceiling limit value: 5 mg/m <sup>3</sup> as Mn
REL	Short-term value: 3 mg/m <sup>3</sup> Long-term value: 1 mg/m <sup>3</sup> fume, as Mn
TLV	Long-term value: 0.02* 0.1** mg/m <sup>3</sup> as Mn; *respirable **inhalable fraction

### 7440-21-3 Silicon

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	TLV withdrawn

### 7440-50-8 Copper

PEL	Long-term value: 1* 0.1** mg/m <sup>3</sup> as Cu *dusts and mists **fume
REL	Long-term value: 1* 0.1** mg/m <sup>3</sup> as Cu *dusts and mists **fume
TLV	Long-term value: 1* 0.2** mg/m <sup>3</sup> *dusts and mists; **fume; as Cu

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· Personal protective equipment

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing and wash before reuse. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

· **Breathing equipment:**



Suitable respiratory protective device recommended

Use NIOSH approved or equivalent fume respirator or air supplied respirator when welding, brazing, cutting, grinding, or soldering in a confined space or general work area where local exhaust and/or ventilation does not keep exposure below the limits outlined in Section 8. Monitor the air quality inside the welder's helmet, and/or worker's breathing zone to determine if a respirator is required and the type needed.

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

• **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

• **Eye protection:**



Tightly sealed goggles

Wear a helmet or face shield with a filter lens around shade number 14. Adjust if needed by selecting the next lighter or darker shade number. See ANSI/ASC Z49.1 Section 4.2 or publication F2.2. Shield other workers by providing screens and flash goggles.

• **Body protection:**

Wear approved head, hand, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. This would include wearing welder's gloves and a protective face shield and may include arm protectors, apron, hats, shoulder protection, as well as dark, non-synthetic, substantial clothing. See ANSI Z49.1. Welders should be trained not to allow electrically live parts to contact the skin or wet clothing and gloves. The welders should insulate themselves from the work and ground and should not touch live electrical parts. Welders should not wear short sleeve shirts or short pants.

**Limitation and supervision of exposure into the environment: None**

## SECTION -9 PHYSICAL AND CHEMICAL PROPERTIES

• **Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Solid Wire/Rod
<b>Colour:</b>	Copper or silver/gray metallic color
<b>Odour:</b>	Odourless until used
<b>Odour threshold:</b>	Not determined.
<b>pH-value:</b>	Not applicable.
<b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Not determined.
<b>Boiling point/Boiling range:</b>	Not determined.
<b>Flash point:</b>	None
<b>Flammability (solid, gaseous):</b>	Not determined.





Welder's First Choice

# SAFETY DATA SHEET

PAGE 7

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

<b>Ignition temperature:</b>	Not applicable
<b>Decomposition temperature:</b>	Not determined.
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	Product does not present an explosion hazard.
<b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Vapor pressure:</b>	Not applicable.
<b>Density:</b>	
<b>Relative density:</b>	Not determined.
<b>Vapor density:</b>	Not applicable.
<b>Evaporation rate:</b>	Not applicable.
<b>Solubility in / Miscibility with:</b>	
<b>Water:</b>	Insoluble.
<b>Partition coefficient (n-octanol/water):</b>	Not determined.
<b>Viscosity:</b>	
<b>Dynamic:</b>	Not applicable.
<b>Kinematic:</b>	Not applicable.
<b>Solvent content:</b>	
<b>VOC content:</b>	0.00 %
<b>Solids content:</b>	100 %
<b>Other information:</b>	No further relevant information available.

## SECTION -10 STABILITY AND REACTIVITY

- Reactivity: Stable under normal conditions.
- Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: Contact with acids or strong bases may cause generation of gas.
- Conditions to avoid: No further relevant information available.
- Incompatible materials: Strong acids, strong bases, strong oxidizing agents and strong reducing agents.
- Hazardous decomposition products:

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the processes and procedures followed, and the welding consumables used. Other conditions that also influence the composition and quantity of fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders in operation and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, and the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapours from cleaning and degreasing procedures). When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 8. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. The known gases and fumes that may form during welding or cutting and their exposure limits are noted in the list in Section 11 below. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 8, plus those from the base metal and coating, etc. as noted above. Chlorinated solvents may be decomposed into toxic gases such as phosgene.

It is understood, however, that the elements and/or oxides to be mentioned are virtually always present as complex oxides and not as metals (See "Characterization of Arc Welding Fume", from the American Welding Society). The elements or oxides listed Section 8 correspond to the ACGIH categories found in "Threshold Limit Values for Chemical Substances and Physical Agents" listed in Section 8. Some products will also contain: silicon, manganese, copper and iron. Some elements or compounds may exceed their PELs/TLVs before the total fumes exceed 5 mg/m<sup>3</sup>.



# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

Welder's First Choice

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

## SECTION -11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects:

Effects of Over-Exposure: Electric arc welding may create one or more of the following health hazards:

- ARC RAYS can injure eyes and burn skin. Incidences of skin cancer have been reported.
- ELECTRIC SHOCK can kill.
- FUMES AND GASES GENERATED FROM WELDING can be dangerous to your health.
- PRIMARY ROUTES OF ENTRY are the respiratory system, eyes, skin, and/or indigestion.
- NOISE can damage hearing

### Short-term (acute) over-exposure effects:

· WELDING FUMES may result in discomfort, such as dizziness, nausea, or dryness or irritation of the nose, throat, or eyes.

· IRON, IRON OXIDE have no known effects. Treat as a nuisance dust or fume.

· MANGANESE, MANGANESE COMPOUNDS may cause metal fume fever, characterized by irritation of the throat, vomiting, nausea, fever, body aches, and chills. Recovery is generally complete within 48 hours of overexposure. COPPER, COPPER OXIDE may cause capillary damage, headache, cold sweat, weak pulse, and kidney and liver damage, central nervous system excitation followed by depression, jaundice, convulsions, paralysis, and coma. Death may occur from shock or renal failure

Long-term (chronic) over-exposure effects:

· WELDING FUMES in excess levels may cause bronchial asthma, lung fibrosis, pneumoconiosis, or 'siderosis.' Overexposure to air contaminants may lead to their accumulation in the lungs, a condition which may be seen as dense areas on chest x-rays. The severity of the change is proportional to the length of exposure. The changes seen are not necessarily associated with symptoms or signs of reduced lung function or disease. In addition, the changes on X-rays may be caused by non-work factors such as smoking, etc.

· IRON, IRON OXIDE may cause siderosis or deposits of iron in the lungs, which is believed to affect pulmonary function. Lungs will clear in time when exposure to iron fumes and its compounds ceases. Iron and magnetite (Fe3O4) are not regarded as fibro genic materials.

· MANGANESE, MANGANESE COMPOUNDS may cause central nervous system effects referred to as 'manganism.' Symptoms include languor, sleepiness, muscular weakness, emotional disturbances, spastic gait, and tremors. Behavioural changes and changes in handwriting may also appear. These effects are irreversible. Employees overexposed to manganese should receive regular medical examinations for early detection of manganism.

· COPPER, COPPER OXIDE may cause hepatic cirrhosis, brain damage and demyelination, kidney defects, and copper deposition in the cornea as exemplified by humans with Wilson's disease. It has also been reported that copper poisoning has lead to haemolytic anaemia and accelerates arteriosclerosis.

### Acute toxicity:

#### LD/LC50 values that are relevant for classification:

#### 7439-89-6 Iron

Oral	LD50	7,500 mg/kg (Rat)
------	------	-------------------

#### 7439-96-5 Manganese

Oral	LD50	9,000 mg/kg (Rat)
------	------	-------------------

#### 7440-21-3 Silicon

Oral	LD50	3,160 mg/kg (Rat)
------	------	-------------------





# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

Welder's First Choice

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

**· Primary irritant effect:**

**· On the skin:**

Irritant to skin and mucous membranes.

**· On the eye:**

Irritating effect

**· Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Symptoms of systemic copper poisoning may include: capillary damage, headache, cold sweat, weak pulse, and kidney and liver damage, central nervous system excitation followed by depression, jaundice, convulsions, paralysis, and coma. Death may occur from shock or renal failure. Chronic copper poisoning is typified by hepatic cirrhosis, brain damage and demyelination, kidney defects, and copper deposition in the cornea as exemplified by humans with Wilson's disease. It has also been reported that copper poisoning has led to haemolytic anaemia and accelerates arteriosclerosis

**· Carcinogenic categories:**

**· IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

**NTP (National Toxicology Program):**

None of the ingredients are listed.

**OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed

## SECTION -12 ECOLOGICAL INFORMATION

**Toxicity:**

**Aquatic Toxicity:**

7439-96-5 Manganese

EC50	40 mg/l (Water flea)
------	----------------------

7440-50-8 Copper

EC50	0.04-0.05 mg/l (Water flea)
------	-----------------------------

**· Persistence and degradability:** No further relevant information available.

**· Behaviour in environmental systems:**

**· Bio accumulative potential:** No further relevant information available.

**· Mobility in soil:** No further relevant information available.

**· Additional ecological information:**

**· General notes:**

Do not allow undiluted product or product that has not been neutralized to reach groundwater, water course or sewage system.

**· Results of PBT and vPvB assessment:**

**· PBT:** Not applicable.

**· vPvB:** Not applicable.

**Other adverse effects:** No further relevant information available



# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

Welder's First Choice

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

## SECTION -13 DISPOSAL CONSIDERATIONS

·Waste treatment methods

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

·**Uncleaned packaging Recommendation :** Disposal must be made according to official regulations

## SECTION -14 TRANSPORT INFORMATION

·UN-Number:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es):

·DOT, ADR/ADN, ADN, IMDG, IATA

· Class: Non-Regulated Material

· Packing group:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

· Environmental hazards: Not applicable.

· Special precautions for user: Not applicable.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

UN "Model Regulation": Non-Regulated Material

## SECTION -15 REGULATORY INFORMATION

·Safety, health and environmental regulations/legislation specific for the substance or mixture:

·SARA (Superfund Amendments and Reauthorization):

**Section 355 (extremely hazardous substances):**

None of the ingredients are listed

**Section 313 (Specific toxic chemical listings):**

7439-96-5	Manganese
7440-50-8	Copper

**TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

**Hazardous Air Pollutants**

7439-96-5	Manganese
-----------	-----------

· **California Proposition65:**

**Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.



Welder's First Choice

# SAFETY DATA SHEET

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

**Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

**New Jersey Right-to-Know List:**

7439-96-5	Manganese
7440-21-3	Silicon
7440-50-8	Copper

**New Jersey Special Hazardous Substance List:**

7439-96-5	Manganese	F3, R1
7440-21-3	Silicon	F3

**Pennsylvania Right-to-Know List:**

7439-96-5	Manganese
7440-21-3	Silicon
7440-50-8	Copper

**Pennsylvania Special Hazardous Substance List:**

7439-96-5	Manganese	E
7440-50-8	Copper	E

**Carcinogenic categories:**

**EPA (Environmental Protection Agency):**

7439-96-5	Manganese	D
7440-50-8	Copper	D

**TLV (Threshold Limit Value established by ACGIH):**

None of the ingredients are listed.

**NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

**GHS label elements**

The product is classified and labelled according to the Globally Harmonized System(GHS).

**Hazard pictograms:**





Welder's First Choice

# SAFETY DATA SHEET

PAGE 12

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

· **Signal word: Warning**

· **Hazard-determining components of labelling:**

Iron

Copper

**Hazard statements:**

**H315+H320:** Causes skin and eye irritation.

**H335:** May cause respiratory irritation.

**Precautionary statements:**

**P261:** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P264:** Wash thoroughly after handling.

**P271:** Use only outdoors or in a well-ventilated area.

**P280:** Wear protective gloves.

**P302+P352:** If on skin: Wash with plenty of water.

**P304+P340:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**P305+P351+P338:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P312:** Call a poison centre/doctor if you feel unwell.

**P321:** Specific treatment(see supplementary first aid instructions on this Safety Data Sheet).

**P362+P364:** Take off contaminated clothing and wash it before reuse.

**P332+P313:** If skin irritation occurs: Get medical advice/attention.

**P337+P313:** If eye irritation persists: Get medical advice/attention.

**P403+P233:** Store in a well-ventilated place. Keep container tightly closed.

**P405:** Store locked up.

**P501:** Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

None of the ingredients are listed.

· **Information about limitation of use:**

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION -16 OTHER INFORMATION

**ROYALE WELD WELL** urges each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond ROYALE WELDWELL's control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and Local laws and regulations remain the responsibility of the user.

· Date of last revision/ revision number: 12/20/2019 / 3

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)



Welder's First Choice

# SAFETY DATA SHEET

PAGE 13

OSHA HAZCOM STANDARD 29 CFR 1910.1200(G) AND GHS REV 03

ISSUE DATE 12/20/2019

REVIEWED ON 12/20/2019

TRADE NAME: CARBON AND LOW-ALLOY STEEL RODS FOR OXYFUEL GAS WELDING

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio accumulative and Toxic

vPvB: very Persistent and very Bio accumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Sol. 1: Flammable solids – Category 1

Flam. Sol. 2: Flammable solids – Category 2

Pyr. Sol. 1: Pyrophoric solids – Category 1

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 3: Hazardous to the aquatic environment – acute aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment – long-term aquatic hazard – Category 4

**\* Data compared to the previous version altered**



Welder's First Choice